



Shell Helix *Extra ECT C3 5W-30*

Fully synthetic motor oil - Enhance your engine's efficiency by reducing friction for optimized performance

Shell Helix Extra ECT uses Anti-Friction Technology that helps to reduce engine frictions to provide enhanced fuel economy and protection. With advanced emissions-compatible technology, it helps to keep diesel particulate filters clean to help maintain engine performance.

DESIGNED TO MEET CHALLENGES

Main Applications

- Shell Helix Extra ECT C3 5W-30 fully synthetic motor oil uses Shell's advanced emissions-compatible technology to help protect the vehicle's emission system. Its low-SAPs formulation helps to keep diesel particulate filters clean and protects them from ash build-up that can block the exhaust system and lead to reduced engine performance.
- Shell Helix Extra ECT can be used for modern gasoline engines, diesel engines with particulate filters and gas engines.

Specifications, Approvals & Recommendations

- ACEA C3
- MB-Approval 229.51
- BMW LL-04
- To find the right Shell Helix product for your vehicles and equipment, please consult Shell LubeMatch at <http://lubematch.shell.com>
- Advice on applications not covered here may be obtained from your Shell or Shell Lubricants distributor representatives or technical helpdesks

Typical Physical Characteristics

Properties			Method	Shell Helix Extra ECT C3 5W-30
Kinematic Viscosity	@100°C	cSt	ASTM D445	12.1
Kinematic Viscosity	@40°C	cSt	ASTM D445	69
Density	@15°C	kg/m ³	ASTM D4052	836.1
Flash Point		°C	ASTM D92	238
Pour Point		°C	ASTM D97	-45

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

• Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet (SDS) which can be obtained from <http://www.epc.shell.com/>

• Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.